



Data subject to change without notice. Always confirm the data is correct from the seller.

# KEM 4160 MF11

## KEM Polycarbonate 10-630A

- IP66; Enclosure types U2, U3, U4
- IP65; Enclosure types MF11, MF03, MF04
- Self-extinguishing material
- Wide operating temperature range
- Padlockable with 3 locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good UV resistance
- Good resistance against many chemicals
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here.**

**KEM 16-40 A Installation guide video**  
>>

**KEM 63-80 A Installation guide video**  
>>

**Technical datasheet** >>

Accessories



## Product details

<b>SKU</b>	KEM 4160 MF11
<b>AC-21 400/415 V (A)</b>	160 A
<b>AC-21 690 V (A)</b>	160 A
<b>AC-22 400/415 V (A)</b>	160 A
<b>AC-22 690 V (A)</b>	160 A
<b>AC-23 400/415 V (A/kW)</b>	160 A / 90 kW
<b>AC-23 690 V (A/kW)</b>	100 A / 90 kW
<b>Cable Area to Switch Terminal (mm<sup>2</sup>) / Bolt size</b>	6-70
<b>Color</b>	Standard
<b>EAN</b>	6419410323502
<b>Enclosure</b>	MF11
<b>Enclosure Type</b>	Polycarbonate
<b>IP Rating</b>	65
<b>Number of Poles</b>	4
<b>Operation</b>	Front-operated
<b>Switch type</b>	Load Break Switch
<b>Weight (kg)</b>	3.4

## Dimensional drawing

