



KEM 425 M2ABS

KEM ABS 10-80A

- IP65
- Recommended for indoor installation only
- Padlockable with three locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good resistance against many chemicals
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

KEM 16-40 A Installation video guide

>>

KEM 63-80 A Installation video guide

>>

Technical datasheet >>

Accessories



Data subject to change without notice. Always confirm the data is correct from the seller.

Product details

SKU	KEM 425 M2ABS
AC-21 400/415 V (A)	40 A
AC-21 690 V (A)	40 A
AC-22 400/415 V (A)	25 A
AC-22 690 V (A)	25 A
AC-23 400/415 V (A/kW)	25 A / 11 kW
AC-23 690 V (A/kW)	25 A / 22 kW
Cable Area to Switch Terminal (mm2) / Bolt size	1.5-16
Color	Standard
EAN	6419410481059
Enclosure	M2
Enclosure Type	ABS
IP Rating	65
Number of Poles	4
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	0.5

Dimensional drawing

