



Data subject to change without notice. Always confirm the data is correct from the seller.

KEM 463 M3ABS

KEM ABS 10-80A

- IP65
- Recommended for indoor installation only
- Padlockable with three locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good resistance against many chemicals
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here.**

KEM 16-40 A Installation video guide

>>

KEM 63-80 A Installation video guide

>>

Technical datasheet >>

Accessories



Product details

| | |
|---|-------------------|
| SKU | KEM 463 M3ABS |
| AC-21 400/415 V (A) | 80 A |
| AC-21 690 V (A) | 80 A |
| AC-22 400/415 V (A) | 63 A |
| AC-22 690 V (A) | 63 A |
| AC-23 400/415 V (A/kW) | 40 A / 22 kW |
| AC-23 690 V (A/kW) | 40 A / 37 kW |
| Cable Area to Switch Terminal (mm²) / Bolt size | 2.5-35 |
| Color | Standard |
| EAN | 6419410481332 |
| Enclosure | M3 |
| Enclosure Type | ABS |
| IP Rating | 65 |
| Number of Poles | 4 |
| Operation | Front-operated |
| Switch type | Load Break Switch |
| Weight (kg) | 0.7 |

Dimensional drawing

